Idaho National Laboratory

U.S. Department of Energy's Vehicle Technologies Program

Maui Energy Expo - PHEV Operations and Performance

Jim Francfort

Maui Energy Expo Maui, Hawaii – September 2009

This presentation does not contain any proprietary or sensitive information

AVTA Background and Goals

- The Advanced Vehicle Testing Activity (AVTA) is part of DOE's Vehicle Technologies Program
- The Idaho National Laboratory (INL) and Electric Transportation Engineering Corporation (ETEC) conduct the AVTA. Argonne National Laboratory performs dynamometer testing
- The AVTA goals:
 - Provide benchmark data to technology modelers, research and development programs, vehicle manufacturers (via VSATT), and target and goal setters
 - Assist fleet managers in making informed early adaptor vehicle purchase, deployment and operating decisions



AVTA Testing by Technology

- Plug-in hybrid electric vehicles (PHEV)
 - 12 models, 187 vehicles, 850,000 fleet test miles
- Hybrid electric vehicles (HEV)
 - 17 models, 45 vehicles, 4.5 million test miles
- Neighborhood electric vehicles
 - 23 models, 200,000 test miles
- Hydrogen ICE (internal combustion engine) vehicles

elec

- 7 models, 500,000 test miles
- Full-size battery electric vehicles (BEVs)
 - 40 EV models, 5+ million test miles
- Urban electric vehicles
 - 3 models, 1 million test miles









12 PHEVs Models in Testing/Demonstrations

- Hymotion Prius (A123Systems)
- Hymotion Escape (A123Systems)
- Ford E85 Escape (Johnson Controls/Saft)
- EnergyCS Prius, 2 models (Valance and Altair Nano)
- Electrovaya Escape (Electrovaya)
- Hybrids Plus Escape, 2 models (Hybrids Plus and K2 Energy Solutions)
- Hybrids Plus Prius (Hybrids Plus)
- Manzanita Prius (lead acid)
- Manzanita Prius (Thunder Sky)
- Renault Kangoo (Saft NiCad)
- (All batteries are Lithium unless noted)





PHEV Testing Methods and Objectives

- Perform independent testing of PHEVs, using:
 - Baseline performance testing: closed test tracks and dynamometers
 - Accelerated testing: dedicated drivers operating on defined onroad loops
 - Fleet testing: everyday unstructured \ non-directed fleet and public use, with onboard data loggers
 - Laboratory testing of PHEV batteries
- Testing used to document:
 - Battery life, charging patterns and profiles
 - Vehicle operations, fuel use (electricity and gasoline) and infrastructure requirements
 - Driver influences on fuel use
 - Individual PHEV models and PHEV concepts
 - PHEV life-cycle costs



PHEV Operating Modes


- <u>Charge sustaining (CS)</u> mode: from start to finish of a single trip, there is no energy available for electric drive propulsion in the PHEV battery. Therefore, the battery state-of-charge (SOC) is <u>sustained</u>
- <u>Charge depleting (CD)</u> mode from start to finish of a single trip, there is energy available for partial or full electric drive propulsion in the PHEV battery. Therefore, the battery SOC is being <u>depleted</u> during the trip
- <u>Mixed CD/CS</u> mode there is energy in the battery pack at the start of a single trip, but the PHEV battery is fully depleted before the trip ends





Hymotion Prius Gen I – UDDS Fuel Use


• 5 kWh A123Systems (Li) and Prius packs (AC kWh)



7

Hymotion Prius Gen I – HWFEDS Fuel Use

• 5 kWh A123Systems (Li) and Prius packs (AC kWh)



PHEV Accelerated Testing

- Accelerated testing in Phoenix over 5,440 onroad miles
- GPS units track distance, average and maximum speeds

Cycle	Urban	Highway	Charge	Reps	Total	Reps	Miles
(mi)	(10 mi)	(10 mi)	(hr)	(N)	(mi)	(%)	(%)
10	1	0	4	60	600	37%	11%
20	1	1	8	30	600	19%	11%
40	4	0	12	15	600	9%	11%
40	2	2	12	15	600	9%	11%
40	0	4	12	15	600	9%	11%
60	2	4	12	10	600	6%	11%
80	2	6	12	8	640	5%	12%
100	2	8	12	6	600	4%	11%
200	2	18	12	3	600	2%	11%
Total	2,340	3,100	1,344	162	5,440		
Average	43%	57%	8.3	18			



Hymotion Prius Gen I – Accelerated Testing

Cycle	Urban	Highway	Charge	Reps	Total	Electricity	Gas	oline
(mi)	(10 mi)	(10 mi)	(hr)	(N)	(mi)	AC kWh	Gals	MPG
10	1	0	4	60	600	136.33	4.81	127.2
20	1	1	8	30	600	122.02	5.37	115.9
40	4	0	12	15	600	84.10	6.05	101.1
40	2	2	12	15	600	87.22	5.78	106.9
40	0	4	12	15	600	79.82	8.54	73.1
60	2	4	12	10	600	55.33	8.98	68.9
80	2	6	12	8	640	43.99	11.36	58.3
100	2	8	12	6	600	35.98	8.43	73.2
200	2	18	12	3	600	15.0	11.02	54.8
Total	2340	3100	1404	167	5,440	Weighted Average		79.5

Each total distance slightly greater than 600 and 640 miles. HEV version = 44 mpg




Hymotion Prius Gen II – Accelerated Testing

Cycle	Urban	Highway	Charge	Reps	Total	Electricity	Gasoline		Recalculated without incomplete
(mi)	(10 mi)	(10 mi)	(hr)	(N)	(mi)	AC kWh	Gals	MPG	charges
10	1	0	4	60	600	111.43	5.205	117.6	
20	1	1	8	30	600	124.50	8.105	80.1	
40	4	0	12	15	600	71.28	9.8	62.1	64.2
40	4	0	12	15	600	44.97	7.2	84.2	135.6
40	2	2	12	15	600	64.36	9.70	64.3	65.5
40	2	2	12	15	600	75.14	6.20	99.8	101.7
40	2	2	12	15	600	70.98	6.83	90.6	98.9
40	0	4	12	15	600	75.18	6.10	103.3	100.0
40	0	4	12	15	600	63.46	8.88	70.8	92.4
60	2	4	12	10	600	33.38	10.54	58.8	
80	2	6	12	8	640	41.38	10.71	61.8	
100	2	8	12	6	600	26.48	10.91	56.5	
200	2	18	12	3	600	16.01	10.41	57.7	
Total	2340	3100	1404	167	7,840	Weighted A	Average		

Each total distance slightly greater than 600 and 640 miles. HEV version = 44 mpg

Hymotion Prius Gen II – Accelerated Testing

40 mile city/highway loops – high ambient temperatures results in incomplete charging



elec

ETEC Hymotion Prius: 40 mi City/Hwy Loops

12

ENERG

kidalas National Laborata


PHEV Fleet Testing Partners

- 75+ testing partners in the U.S. and Canada:
 - 36 Electric utilities and 2 clean-air agencies
 - 10 City, county and state governments
 - 7 Private companies and advocacy organizations
 - 8 Universities and colleges and 4 Canadian provinces
 - 2 PHEV companies 1 sea port and 1 DOD facility
- Testing partners include:
 - A123Systems, EnergyCS, NYSERDA, NRECA, UC Davis, Fairfax County, Google.org, Austin Energy, Central Vt PSC, Duke Energy, Advanced Energy, Progress Energy, SDGE, Basin Electric, Buckeye Power, WI Public Power Inc., Madison GE, SCANA Corp., HCATT, BC Hydro, BC Government, various Washington State groups





PHEVs and Demonstration Locations




PHEV Fleet Testing Reports


- Summary reports posted monthly on web
- Individual vehicle reports only go to the respective fleets each month, 1,060+ reports to date (August 1, 2009)
- 153 Hymotion Prius PHEVs, 780,000 miles, 86,000 trips, 20,500 charging events, 47,000 kWh used. V2Green and Kvaser data logger reports





Hymotion Prius (V2Green Logger) Fleet Tests

March 01/08 to July 01/09. 110 PHEVs, 498,000 miles, 54,000 trips, 12,400 charging events and 31,000 kWh used










Kidala National Laborator

elec

ENERGY

Hymotion Prius PHEVs – CS Trips

• MPG and aggressive driving impacts March '08 – May '09




Data from 150 Hymotion Prius with V2Green and Kvaser loggers





Hymotion Prius PHEVs – CS/CD Mixed Trips

• MPG and aggressive driving impacts March '08 – May '09




elec

Data from 150 Hymotion Prius with V2Green and Kvaser loggers

Idales National Laborator

Hymotion Prius PHEVs – CD Trips

• MPG and aggressive driving impacts March '08 – May '09




Data from 150 Hymotion Prius with V2Green and Kvaser loggers





19

MPG Results - Charge Depleting (CD) Mode




Data from 150 Hymotion Prius with V2Green and Kvaser loggers






Ambient Temperature MPG Impacts



Engine Operations by Ambient Temperatures




elec

ENERGY


idala National Laboratory

Monthly Fleet Testing MPG Results





Testing Results by Fleet




elec Idales National Leboratory




ENERGY

Testing Results by Fleet – cont'd




Testing Results by Fleet – cont'd



 ENERGY

Testing Results by Fleet – cont'd



PHEV Charging Infrastructure Cost Report

- Analyzes PHEV infrastructure requirements in single and multi-family residential, and commercial facilities as well as driving trends. No site specific costs
- Charging infrastructure equipment/administrative costs:
 - Levels 1 (120V, 15 or 20 amp) and 2 residential
 - Levels 1 and 2 (208/240V ~40 amp) apartment complex
 - Level 2 commercial facility
- Battery sizes & charge times for various PHEV platforms
- Power electronics & battery costs for PHEV platforms


Level 1 Residential	Labor	Material	Permits	Total
EVSE (charge cord)		\$250		\$250
Residential circuit installation (20A branch circuit, 120 VAC/1-Phase)	\$300	\$131	\$85	\$516
Administration costs	\$60	\$43	\$9	\$112
Total Level 1 Cost	\$360	\$424	\$94	\$878

Report @ http://avt.inl.gov/pdf/phev/phevInfrastructureReport08.pdf elec



ENERGY

AVTA Webpage Use and Gasoline Costs



29

Acknowledgement

This work is supported by the U.S. Department of Energy's Vehicle Technologies Program

Additional Information

http://avt.inl.gov or http://www1.eere.energy.gov/vehiclesandfuels/avta/

INL/CON-09-16669



30